

FGT. We proposed a novel algorithm to compute the minimum mosaic structure of genomes. the efficiency of our algorithm allows for genome-wide analysis.

References

1. Gusfield,D. (2005) Optimal, efficient reconstruction of root-unknown phylogenetic networks with constrained and structured recombination, *Journal of Computer and System Sciences*, **70**, 381-398.
2. Hudson,R., Kaplan,N. (1985) Statistical properties of the number of the recombination events in the history of a sample of DNA sequences, *Genetics*, **111**, 147-164.
3. Kreitman,M. (1983) Nucleotide polymorphism at the alcohol dehydrogenase locus of *Drosophila melanogaster*, *Nature*, **304**, 412-417.
4. Moore,K., Zhang,Q, McMillan,L., Wang,W., Pardo-Manuel de Villena,F. (2008) Genome-wide compatible SNP intervals and their properties, UNC Tech Report, June 08.
5. Myers,S.R., Griffiths,R.C. (2003) Bounds on the minimum number of recombination events in a sample history, *Genetics*, **163**, 375-394.
6. Schwartz,R., Halldorson,B.V., Bafna,V., Clark,A.G., Istrail,S. (2003) Robustness of inference of haplotyp block structure, *J. Comput. Biol.*, **10**, 13-19.
7. Song,Y.S., Wu,Y, Gusfield,D. (2005) Efficient computation of close lower and upper bounds on the minimum number of recombinations in biological sequence evolution, *Bioinformatics*, **21**, i413-i422.
8. Song,Y.S., Hein,J. (2005) Constructing minimal ancestral recombination graphs, *J. Comput. Biol.*, **12(2)**, 147-169.
9. Song,Y.S., Hein,J. (2003) Parsimonious reconstruction of sequence evolution and haplotype blocks: finding the minimum number of recombination events, *Proceedings of the Third International Workshop on Algorithms in Bioinformatics (WABI 2003)*, 287-302.
10. Szatkiewicz,J.P., Beane,G.L., Ding,Y., Hutchins,L., Pardo-Manuel de Villena,F., Churchill,G. (2008) An imputed genotype resource for the laboratory mouse, *Mamm Genome*, 19:199.
11. Ukkonen, E. (2002) Finding founder sequences from a set of recombinants, *WABI 2002*, 277-286.
12. Wang,L., Zhang,K., Zhang,L. (2001) Perfect phylogenetic networks with recombination, *J. Comput. Biol.*, **8**, 69-78.
13. Wu, Y., Gusfield, D. (2007) Improved algorithms for inferring the minimum mosaic of a set of recombinants, *CPM 2007*, 150-161.
14. Zhang,K., Deng,M., Chen,T., Waterman,M.S., Sun,F. (2003) A Dynamic programming algorithm for haplotype block partitioning, *PNAS.*, **99**, 7335-7339.
15. Zhang, Q., Wang, W., McMillan, L., Villena, F.P., Threadgill, D. (2008) Inferring genome-wide mosaic structure, UNC Tech. Report (2008).
16. <http://cgd.jax.org/ImputedSNPData/imputedSNPs.htm>.